

AVI202

Network Camera

(D&N)



• FEATURES

- (1) Low-latency video streaming for sharp and clear images
- (2) Hybrid digital / analog video output
- (3) Motion detection and alarm notification functions
- (4) External microphone in / audio out for two-way voice communication
- (5) Day/night functionality
- (6) High quality image sensor
- (7) Complete IP surveillance system, such as the Central Management System (CMS) software, Network-Attached Storage (NAS), Network Video Recorder (NVR), etc.

• SPECIFICATIONS

AVI202	
Network	
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Frame Rate	NTSC:30, PAL:25
Number of Online Users	10
Security	Multiple user access levels with password
Web management software	YES (Control up to 16 network cameras simultaneously)
Video / Audio	
Video Compression	MPEG4 / MJPEG
Video Remote Control	YES
Video Adjustment	Brightness, Contrast, Saturation and Hue
Audio Compression	uLaw , 128kbps
Audio Input	Built-in Microphone, External Microphone Input
Audio Output	YES



SPECIFICATIONS (CONTINUED...)

AVI202		
Camera		
Image Sensor	1/3.6" image sensor	
Pixels	738(H) x 480(V)	
Lens	f3.6mm	
F-number	F2.0	
Viewing Angle	80°	
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.	
IR LED	YES	
Min Illumination	1 Lux / F2.0; 0 Lux (10m IR ON)	
Video Output	1.0 Vp-p. 75Ω	
BLC	AUTO	
White Balance	ATW	
Others		
Remote Control	YES	
Motion Detection	YES	
Alarm and event Notification	Image upload over FTP and Email	
General I/O	Alarm in x1	
Power	DC12V, 1A	
Operating Temperature	0~40 ℃	
Humidity	85%	
Minimum Web Browsing Requirements	 Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD 256 MB RAM AGP graphics card, Direct Draw, 32MB RAM Windows XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later Internet Explorer 6.x or later 	
Dimension (mm)**	152.5(L) x 115.2(W) x 40.2(H) (6.00" x 4.54" x 1.58")	
Shipping Weight	812g (1.79 lbs) including mounting bracket and power supply	
In/Out Door Use	Indoor	

* The specifications are subject to change without notice. ** Dimensional tolerance: (± 5mm)

•

Dimensions: 152.5 (L) x 115.2 (W) x 40.2 (H) mm



