

**EV-IL115 INFRARED INDUCTOR**

### ⦿ Main Function

- ▶ Combined with B/W or special color camera, it can monitor target in low illuminance condition, even darkness

### ⦿ Mounting

- ▶ Mount on the Pan/Tilt or Pan, scan with camera
- ▶ Mount with the camera under the same direction

### ⦿ Technical Specifications

- |                         |  |
|-------------------------|--|
| ▶ Power Input           | : AC 220V/50Hz                         |
| ▶ Consumption           | : 25W                                  |
| ▶ Open Mode             | : Light dependent resist, Auto control |
| ▶ Transmission Wave     | : 880 nm                               |
| ▶ Transmission Angle    | : 30° Horizontal / Vertical            |
| ▶ Transmission Distance | : 0 ~ 50m                              |
| ▶ Operation Temperature | : -20° C ~ +60° C                      |
| ▶ Dimensions (Ø x L)    | : 250(W) x 153(D) x 110(H) mm          |
| ▶ Weight                | : 2750 gr.                             |



## KVAZER Ltd

E-mail: [sales@kvazer.com](mailto:sales@kvazer.com)  
Web site: [kvazer.com](http://kvazer.com)

12 Kuklensko Shosse Str.  
4004 Plovdiv, Bulgaria  
Tel. +359 32 675 134  
Fax: +359 32 670 443