

LS-9004H

Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out

* Audio Input/Output: RCA 4CH In/ 1CH Out

* Alarm Input/Output: Alarm 4CH In/ 1CH Out

* Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)

* Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4

* Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback

* 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software

* Remote Control, PTZ, RS485 x 1, 2 × USB, 1 × IR Controller

* 1 SATA Hard Disk interface



Model	LS-9004H
Compression Format	H.264
Operating System	Embedded LINUX Operating System
User Interface	16-bit true color graphical menu, support for USB mouse operation, with menu notes
Preview resolution	720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1x4
Real time recording support	CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)
Video Input/Output	BNC 4CH In/ 1CH BNC Out/ 1CH VGA Out
Audio Input/Output	RCA 4CH In/ 1CH Out
Alarm Input/Output	Alarm 4CH In/ 1CH Out
Monitor Screen	1 / 4 screen display, PAL D1: 704*576
Local Playback	4CH synchronized playback
Motion Detection	PAL 13*10 (130) ; NTSC 13*8 (104) 4 grade available
Communication Interface	1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
Hard Disk	1 SATA Hard Disc interface
USB port	2pc (Mouse port and USB2.0 port)
VGA port	1pc(optional) Resolution:800×600,1024×768
Special Feature	Support remote view by Mobilephone
Power Source	19V/3A
Working Temperature	0℃-- +55℃
Working Humidity	10%--90%
Dimension	L280 x W229 x H43mm
Weight	3.0Kg