

LS-9008H

*Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out

*Audio Input/Output: RCA 8CH In/ 1CH Out

*Alarm Input/Output: Alarm 4CH In/ 1CH Out

*Compression Method: H.264

*Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 60 Fps (NTSC); 704×576 with 50 Fps (PAL)

*Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: CIF x 8 / D1 x 1

*Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback

*Hi-speed backup/upgrade/record via USB2.0

*1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software

*Remote Control, PTZ, RS485 x 1, 2 × USB, 1 × IR Controller



Model	LS-9008H
Compression Format	H.264
Video System	NTSC / PAL
Video Input/Output	BNC 8CH In/ 1CH BNC Out/ 1CH VGA Out
Audio Input/Output	RCA 8CH In/ 1CH Out
Alarm Input/Output	Alarm 4CH In/ 1CH Out
Preview resolution	720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: CIF x 8 / D1 x 1
Real time recording support	CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)
Video Compression Rate	CIF Resolution, 3 grade available
Audio Compression	8kHz*16bit, ADPCM
Motion Detection	1 / 4 screen display, PAL D1: 704*576
Communication Interface	1pc RJ45 10M/100M Ethernet, 1pc port, 1pc RS485 port
Hard Disk	1 SATA Hard Disk interface
USB port	2pc (Mouse port and USB2.0 port)
Network Protocol	TCP/IP、PPPOE 、DDNS and NTP
VGA port	1pc(optional) Resolution:800×600,1024×768
Special Feature	Support GPRS/CDMA/EDGE/3G mobile phone view
Power Supply	12V/3A
Working Temperature	0℃--+55℃
Working Humidity	10%--90%
Dimension	L280 x W229 x H43mm
Weight	4.2Kg